

Replaces: N/A

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

DATE: 29.10.2024 Ref No: 0645.0.BB/DL

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product Name OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE

Pure substance/mixture Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants

Uses advised against None known

#### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Siroflex Limited Dodworth Business Park Dodworth, Barnsley South Yorkshire, S75 3SP

Tel +44 (0)1226 771600 Fax +44 (0)1226 771601

Further information available from: www.ob1original.com

# 1.4. Emergency telephone number

United Kingdom + 44 (0) 1226 771600 (Office Hours Only)
Ireland NPIC - National Poison Information Centre

Members of the Public: +353 (0)1 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (0)1 8092566 (24 hour service)

Europe 112

# **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

## Signal word

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **EU Specific Hazard Statements**

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine & N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine. May produce an allergic reaction EUH210 - Safety data sheet available on request

United Kingdom - BE Page 1 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

#### 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

# **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	EC No (EU	CAS No	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
Trimethoxyvinylsilane	220-449-8	2768-02-7	Acute Tox. 4 (H332)	-	-	-	01-2119513215-
1 - <2.5 %	(014-049-00-		Skin Sens. 1B (H317)				52-XXXX
	0)		Flam. Liq. 3 (H226)				
N-(3-(trimethoxysilyl)pro	217-164-6	1760-24-3	Eye Dam. 1 (H318)				01-2119970215-
pyl)ethylenediamine	217-104-0	1700-24-3	Skin Sens. 1 (H317)	-	-	_	39-XXXX
0.1- <1 %			Acute Tox. 4 (H332)				007000
			STOT SE 3 (H335)				
Dioctyltin oxide	212-791-1	870-08-6	STOT SE 2 (H371)	-	-	-	01-2119971268-
0.1 - <0.5 %							27-xxxx
N-[3-(Dimethoxymethylsil		3069-29-2	Acute Tox. 4 (H302)	-	-	-	01-2119963926-
yl)propyl]-ethylenediamin			Skin Irrit. 2 (H315)				21-xxxx
e 0.1 - <0.5 %			Eye Dam. 1 (H318) Skin Sens. 1A (H317)				
0.1 - \0.5 /6			OKIII OGIIS. IA (IISTI)				

## Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

Full text of H- and EUH-phrases: see section 16

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

United Kingdom - BE Page 2 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
N-(3-(trimethoxysilyl)pr opyl)ethylenediamine	217-164-6	1760-24-3	-	-	1.5	-	-
Dioctyltin oxide	212-791-1	870-08-6	-	-	-	-	-
N-[3-(Dimethoxymethyl silyl)propyl]-ethylenedia mine		3069-29-2	500	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Small amounts of toxic methanol are released by hydrolysis. Call a doctor immediately.

Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

No information available. **Effects of Exposure** 

4.3. Indication of any immediate medical attention and special treatment needed

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon Note to doctors

> curing. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.

# **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

United Kingdom - BE Page 3 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

chemical

**Specific hazards arising from the** Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** 

Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Silicon

5.3. Advice for firefighters

precautions for fire-fighters

**Special protective equipment and** Wear self contained breathing apparatus for fire fighting if necessary.

## SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Do not get Personal precautions

in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section **Environmental precautions** 

12 for additional Ecological Information.

# 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

Take up mechanically, placing in appropriate containers for disposal. Methods for cleaning up

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

Do not eat, drink or smoke when using this product. Wash hands before breaks and after General hygiene considerations

work.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture.

Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

#### 7.3. Specific end use(s)

#### Specific use(s)

Adhesives and/or sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

4 / 15 United Kingdom - BE Page

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

Other information Observe technical data sheet.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon **Exposure Limits** curing

Chemical name	European Union	United Kingdom
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m³ *	TWA: 200 ppm TWA: 266 mg/m³ STEL: 250 ppm STEL: 333 mg/m³ Sk*
Dioctyltin oxide 870-08-6	-	TWA: 0.1 mg/m³ STEL: 0.2 mg/m³ Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
67-56-1		shift)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL) Trimethoxyvinylsilane (2768-02-7)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Systemic health effects Long term	Inhalation	27,6 mg/m³		
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d		

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Systemic health effects Long term	Inhalation	35.5 mg/m³			
worker Systemic health effects Long term	Dermal	5 mg/kg bw/d			

Dioctyltin oxide (870-08-6)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d		
worker Long term Systemic health effects	Inhalation	0.004 mg/m³		

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)					
Туре	Exposure route	Derived No Effect Level	Safety factor		
		(DNEL)	•		
worker	Inhalation	12 mg/m³			
Long term		-			

United Kingdom - BE Page 5 / 15

# **OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE**

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

Systemic health effects			
worker	Dermal	1.7 mg/kg bw/d	
Long term			
Systemic health effects			

<b>Derived No Effect Level (DN</b>	Derived No Effect Level (DNEL)				
Trimethoxyvinylsilane (2768	-02-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³			
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d			
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d			

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Systemic health effects Long term	Oral	2.5 mg/kg bw/d			
Consumer Systemic health effects Long term	Inhalation	8.7 mg/m³			
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d			

Dioctyltin oxide (870-08-6)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m³	

N-[3-(Dimethoxymethylsilyl)	N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Inhalation	2.9 mg/m³				
Consumer Long term Systemic health effects	Dermal	0.83 mg/kg bw/d				
Consumer Long term Systemic health effects	Oral	0.83 mg/kg bw/d				

United Kingdom - BE Page 6 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

# **Predicted No Effect Concentration**

(PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.062 mg/l			
Marine water	0.0062 mg/l			
Sewage treatment plant	25 mg/l			

Dioctyltin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.006 mg/l
Sewage treatment plant	25 mg/l
Freshwater sediment	0.24 mg/kg dry weight
Marine sediment	0.024 mg/kg dry weight
Soil	0.01 mg/kg dry weight

#### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Wear safety glasses with side shields (or goggles). Eye protection must conform to Eye/face protection

standard EN 166.

Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber. Hand protection

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

None under normal use conditions.

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Organic gases and vapours filter conforming to EN 14387. White. Brown. Recommended filter type:

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state Solid **Appearance** Paste Colour White Odour

Characteristic.

Values Remarks • Method Property

Melting point / freezing point No data available None known Initial boiling point and boiling No data available None known

United Kingdom - BE Page 7 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

range

Flammability No data available

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

> 60 °C Flash point

**Autoignition temperature** No data available None known

**Decomposition temperature** None known

No data available

pH (as aqueous solution) No data available None known

Kinematic viscosity > 21 mm<sup>2</sup>/s Dynamic viscosity No data available

Water solubility No data available. Product cures with

moisture

No data available Solubility(ies) None known No data available None known **Partition coefficient** Vapour pressure No data available None known Relative density No data available None known

No data available **Bulk density** 

**Density** 1.54 g/cm<sup>3</sup>

Relative vapour density No data available None known

**Particle characteristics** 

**Particle Size** No information available **Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

**VOC** content No data available 3.6 %

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

## SECTION 10: Stability and reactivity

10.1. Reactivity

Product cures with moisture. Reactivity

10.2. Chemical stability

Stable under normal conditions. Stability

**Explosion data** 

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

United Kingdom - BE Page 8 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

sources of ignition.

10.5. Incompatible materials

None known based on information supplied. Incompatible materials

10.6. Hazardous decomposition products

**Hazardous decomposition** 

None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are

products formed by hydrolysis and released upon curing.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### **Product Information**

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in

susceptible persons.

Based on available data, the classification criteria are not met. Ingestion

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Acute toxicity

#### **Numerical measures of toxicity**

#### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg ATEmix (dermal) >5000 mg/kg >20000 ppm ATEmix (inhalation-gas) ATEmix (inhalation-dust/mist) >5 mg/l ATEmix (inhalation-vapour) 586.80 mg/l

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
	(Rattus) OECD 401	cuniculus)	OECD TG 403
N-(3-(trimethoxysilyl)propyl)eth	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44
ylenediamine			mg/L air
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
		OECD 402	
N-[3-(Dimethoxymethylsilyl)pro	=200 - 2000 mg/Kg (Rattus)	>5000 mg/Kg (Oryctolagus	> 5.2 mg/L (Rattus)4 h
pyl]-ethylenediamine	(OECD 401)	cuniculus)	(OECD 403)
		(OECD 402)	

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Page 9 / 15 United Kingdom - BE

OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE DATE: 29.10.2024	Replaces: N/A Ref No: 0645.0.BB/DL

Trimethoxyvinylsilane (2768-02-7)						
Method Species Exposure route Effective dose Exposure time Results						
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit				Mild skin irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant	
Acute Eye						
Irritation/Corrosion						

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			Eye Damage
Acute Eye					
Irritation/Corrosion					

# Respiratory or skin sensitisation

OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation			were observed

# Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		_

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Method	Species	Results		
OECD Test No. 471: Bacterial Reverse Mutation Test	Mammalian cells in vitro	Negative		
OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hprt and xprt genes	Mammalian cells in vitro	Negative		

## Carcinogenicity

Based on available data, the classification criteria are not met.

## Reproductive toxicity

Based on available data, the classification criteria are not met.

United Kingdom - BE Page 10 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

Trimethoxyvinylsilane (2768-02-7)				
Method	Species	Results		
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable		
Toxicity Study with the				
Reproduction/Developmental Toxicity Screening				
Test				

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Method	Species	Results		
OECD Test No. 422: Combined Repeated Dose	Rat	NOAEL >500 mg/Kg		
Toxicity Study with the	Oral			
Reproduction/Developmental Toxicity Screening				
Test				

STOT - single exposure

Based on available data, the classification criteria are not met.

Dioctyltin oxide (870-08-6)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 422:	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg	
Combined Repeated Dose					bw/d May cause	
Toxicity Study with the					damage to the	
Reproduction/Developme					following organs:	
ntal Toxicity Screening					Immune system	
Test						

# STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422:	Rat	Sub-acute oral		28 days	NOAEL >500 mg/kg
Combined Repeated Dose		toxicity gavage			
Toxicity Study with the					
Reproduction/Developme					
ntal Toxicity Screening					
Test					

Dioctyltin oxide (870-0	08-6)				
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 davs	0.3 -0.5 ma/ka bw/d

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

# 11.2. Information on other hazards

## 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

#### 11.2.2. Other information

United Kingdom - BE Page 11 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A Ref No: 0645.0.BB/DL DATE: 29.10.2024

Other adverse effects No information available.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

## **Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		(iong com)
N-(3-(trimethoxysilyl)pr opyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static		
Dioctyltin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Dappnia magna)) (Daphnia sp. Acute Immobilisation Test)		

## 12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)					
Method	Exposure time	Value	Results		
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily		
Biodegradability: Manometric	-		biodegradable		
Respirometry Test (TG 301 F)			-		

Dioctyltin oxide (870-08-6)					
Method	Exposure time	Value	Results		
OECD Test No. 301F: Ready	755 hours	biodegradation	Not readily biodegradable 2		
Biodegradability: Manometric			%		
Respirometry Test (TG 301 F)					

## 12.3. Bioaccumulative potential

#### Bioaccumulation

**Component Information** 

Chemical name	Partition coefficient	
Trimethoxyvinylsilane	1.1	
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3	
Dioctyltin oxide	6	

# 12.4. Mobility in soil

No information available. Mobility in soil

12.5. Results of PBT and vPvB assessment

United Kingdom - BE Page 12 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Ref No: 0645.0.BB/DL DATE: 29.10.2024

PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the

Replaces: N/A

threshold of declaration.

Chemical name	PBT and vPvB assessment	
Trimethoxyvinylsilane	The substance is not PBT / vPvB	
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB	
Dioctyltin oxide	The substance is not PBT / vPvB	
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	The substance is not PBT / vPvB	

#### 12.6. Endocrine disrupting properties

No information available. **Endocrine disrupting properties** 

#### 12.7. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging

Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated Not regulated 14.3 Transport hazard class(es) 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special precautions for user

**Special Provisions** None

IMDG

Not regulated 14.1 UN number or ID number Not regulated 14.2 UN proper shipping name 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated

14.5 Marine pollutant NP 14.6 Special precautions for user

**Special Provisions** None

14.7 Maritime transport in bulk

according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

# Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated

United Kingdom - BE Page 13 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

DATE: 29.10.2024 Ref No: 0645.0.BB/DL

Replaces: N/A

14.4 Packing group Not regulated14.5 Environmental hazards Not applicable

14.6 Special precautions for user Special Provisions None

## Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### **SVHC:** Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No.	
Dioctyltin oxide	870-08-6	
Methyl alcohol	67-56-1	
Methyl alcohol	67-56-1	

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Dioctyltin oxide	870-08-6	Use restricted. See entry 20.

20 (6) DOT.

# Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

# REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

United Kingdom - BE Page 14 / 15

**OB1 PANELPAL PANELLING ADHESIVE 290ML WHITE** 

Replaces: N/A DATE: 29.10.2024 Ref No: 0645.0.BB/DL

Not applicable

#### **National regulations**

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

## Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

Leaend

TWA (time-weighted average) **TWA STEL** STEL (Short Term Exposure Limit)

Ceilina Ceiling Limit Value Sk\* Skin designation

**SVHC** Substance(s) of Very High Concern

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals **PBT** Very Persistent and very Bioaccumulative (vPvB) Chemicals vPvB

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

**EWC** European Waste Catalogue

European Agreement concerning the International Carriage of Dangerous Goods by ADR

Road

**IMDG** International Maritime Dangerous Goods (IMDG) International Air Transport Association (IATA) IATA

RID Regulations concerning the International Transport of Dangerous Goods by Rail

# Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

**Revision date** 16-Oct-2024

Indication of changes

**Revision Note** SDS sections updated, 2, 3.

**Training Advice** When working with hazardous materials, regular training of operators is required by law

**Further information** No information available

#### This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom - BE Page 15 / 15